

RESOLUTION 76 (REV.WRC-15)

Protection of geostationary fixed-satellite service and geostationary broadcasting-satellite service networks from the maximum aggregate equivalent power flux-density produced by multiple non-geostationary fixed-satellite service systems in frequency bands where equivalent power flux-density limits have been adopted

The World Radiocommunication Conference (Geneva, 2015),

considering

- a)* that WRC-97 adopted, in Article **22**, provisional equivalent power flux-density (epfd) limits to be met by non-geostationary fixed-satellite service (non-GSO FSS) systems in order to protect GSO FSS and GSO broadcasting-satellite service (BSS) networks in parts of the frequency range 10.7-30 GHz;
- b)* that WRC-2000 revised Article **22** to ensure the limits contained therein provide adequate protection to GSO systems without placing undue constraints on any of the systems and services sharing these frequency bands;
- c)* that WRC-2000 decided that a combination of single-entry validation, single-entry operational and, for certain antenna sizes, single-entry additional operational epfd limits, contained in Article **22**, along with the aggregate limits in Tables 1A to 1D as contained in Annex 1 to this Resolution, which apply to non-GSO FSS systems, protects GSO networks in these frequency bands;
- d)* that these single-entry validation limits have been derived from aggregate epfd masks contained in Tables 1A to 1D, assuming a maximum effective number of non-GSO FSS systems of 3.5;
- e)* that the aggregate interference caused by all co-frequency non-GSO FSS systems in these frequency bands into GSO FSS systems should not exceed the aggregate epfd levels in Tables 1A to 1D;
- f)* that WRC-97 decided, and WRC-2000 confirmed, that non-GSO FSS systems in the frequency bands in question are to mutually coordinate the use of frequencies in these frequency bands under the provisions of No. **9.12**;
- g)* that the orbital characteristics of such systems are likely to be inhomogeneous;
- h)* that, as a result of this likely inhomogeneity, the aggregate epfd levels from multiple non-GSO FSS systems will not be directly related to the actual number of systems sharing a frequency band, and the number of such systems operating co-frequency is likely to be small;
- i)* that the possible misapplication of single-entry limits should be avoided,

RES76-2

recognizing

- a) that non-GSO FSS systems are likely to need to implement interference mitigation techniques to mutually share frequencies;
- b) that, on account of the use of such interference mitigation techniques, it is likely that the number of non-GSO systems will remain small, as will the aggregate interference caused by non-GSO FSS systems into GSO systems;
- c) that, notwithstanding *considering d) and e) and recognizing b)*, there may be instances where the aggregate interference from non-GSO systems could exceed the interference levels given in Tables 1A to 1D;
- d) that administrations operating GSO systems may wish to ensure that the aggregate efd produced by all operating co-frequency non-GSO FSS systems in the frequency bands referred to in *considering a)* above into GSO FSS and/or GSO BSS networks does not exceed the aggregate interference levels given in Tables 1A to 1D,

noting

Recommendation ITU-R S.1588 “Methodologies for calculating aggregate downlink equivalent power flux-density produced by multiple non-geostationary fixed-satellite service systems into a geostationary fixed-satellite service network”,

resolves

1 that administrations operating or planning to operate non-GSO FSS systems, for which coordination or notification information, as appropriate, was received after 21 November 1997, in the frequency bands referred to in *considering a)* above, individually or in collaboration, shall take all possible steps, including, if necessary, by means of appropriate modifications to their systems, to ensure that the aggregate interference into GSO FSS and GSO BSS networks caused by such systems operating co-frequency in these frequency bands does not cause the aggregate power levels given in Tables 1A to 1D to be exceeded (see No. **22.5K**);

2 that, in the event that the aggregate interference levels in Tables 1A to 1D are exceeded, administrations operating non-GSO FSS systems in these frequency bands shall take all necessary measures expeditiously to reduce the aggregate efd levels to those given in Tables 1A to 1D, or to higher levels where those levels are acceptable to the affected GSO administration (see No. **22.5K**),

invites the ITU Radiocommunication Sector

1 to continue its studies and to develop , as appropriate, a suitable methodology for calculating the aggregate efd produced by all non-GSO FSS systems operating or planning to operate co-frequency in the frequency bands referred to in *considering a)* above into GSO FSS and GSO BSS networks, which may be used to determine whether the systems are in compliance with the aggregate power levels given in Tables 1A to 1D;

2 to continue its studies and to develop a Recommendation on the accurate modelling of interference from non-GSO FSS systems into GSO FSS and GSO BSS networks in the frequency bands referred to in *considering a)* above, in order to assist administrations planning or operating non-GSO FSS systems in their efforts to limit the aggregate efd levels produced by their systems into GSO networks, and to provide guidance to GSO network designers on the maximum efd levels expected to be produced by all non-GSO FSS systems when accurate modelling assumptions are used;

3 to develop a Recommendation containing procedures to be used among administrations in order to ensure that the aggregate efd limits given in Tables 1A to 1D are not exceeded by operators of non-GSO FSS systems;

4 to attempt to develop measurement techniques to identify the interference levels from non-GSO systems in excess of the aggregate limits given in Tables 1A to 1D, and to confirm compliance with these limits,

instructs the Director of the Radiocommunication Bureau

1 to assist in the development of the methodology referred to in *invites the ITU Radiocommunication Sector 1* above;

2 to report to a future competent conference on the results of studies in *invites the ITU Radiocommunication Sector 1 and 3* above.

ANNEX 1 TO RESOLUTION 76 (REV.WRC-15)

TABLE 1A^{1, 2, 3}

Limits on aggregate epfd↓ radiated by non-GSO FSS systems in certain frequency bands

| Frequency band (GHz) | epfd↓ (dB(W/m ²)) | Percentage of time during which epfd↓ may not be exceeded | Reference bandwidth (kHz) | Reference antenna diameter, and reference radiation pattern ⁴ |
|---|-------------------------------|---|---|--|
| 10.7-11.7 in all Regions 11.7-12.2 in Region 2 12.2-12.5 in Region 3 12.5-12.75 in Regions 1 and 3 | -170 | 0 | 40 | 60 cm Recommendation ITU-R S.1428 |
| | -168.6 | 90 | | |
| | -165.3 | 99 | | |
| | -160.4 | 99.97 | | |
| | -160 | 99.99 | | |
| | -160 | 100 | 40 | 1.2 m Recommendation ITU-R S.1428 |
| | -176.5 | 0 | | |
| | -173 | 99.5 | | |
| | -164 | 99.84 | | |
| | -161.6 | 99.945 | | |
| | -161.4 | 99.97 | | |
| | -160.8 | 99.99 | | |
| | -160.5 | 99.99 | | |
| | -160 | 99.9975 | 40 | 3 m ⁵ Recommendation ITU-R S.1428 |
| | -160 | 100 | | |
| | -185 | 0 | | |
| | -184 | 90 | | |
| | -182 | 99.5 | | |
| | -168 | 99.9 | | |
| | -164 | 99.96 | | |
| -162 | 99.982 | 40 | 10 m ⁵ Recommendation ITU-R S.1428 | |
| -160 | 99.997 | | | |
| -160 | 100 | | | |
| -190 | 0 | | | |
| -190 | 99 | | | |
| -166 | 99.99 | | | |
| -160 | 99.998 | | | |
| -160 | 100 | | | |

¹ For certain GSO FSS receive earth stations, see also Nos. 9.7A and 9.7B.

² In addition to the limits shown in Table 1A, the following aggregate epfd↓ limits apply to all antenna sizes greater than 60 cm in the frequency bands listed in Table 1A:

| 100% of the time epfd↓ (dB(W/(m ² · 40 kHz))) | Latitude (North or South) (degrees) |
|--|-------------------------------------|
| -160 | 0 ≤ Latitude ≤ 57.5 |
| $-160 + 3.4(57.5 - \text{Latitude})/4$ | 57.5 < Latitude ≤ 63.75 |
| -165.3 | 63.75 < Latitude |

³ For each reference antenna diameter, the limit consists of the complete curve on a plot which is linear in decibels for the epfd↓ levels and logarithmic for the time percentages, with straight lines joining the data points.

⁴ For this Table, reference patterns in Recommendation ITU-R S.1428 shall be used only for the calculation of interference from non-GSO FSS systems into GSO FSS systems.

⁵ The values for the 3 m and 10 m antennas are applicable only for the methodology referred to *invites the ITU Radiocommunication Sector 1*.

TABLE 1B^{1, 2, 3}Limits on aggregate epfd_↓ radiated by non-GSO FSS systems in certain frequency bands

| Frequency band (GHz) | epfd _↓ (dB(W/m ²)) | Percentage of time during which epfd _↓ may not be exceeded | Reference bandwidth (kHz) | Reference antenna diameter, and reference radiation pattern ⁴ |
|----------------------|---|---|---------------------------------------|--|
| 17.8-18.6 | -170 | 0 | 40 | 1 m Recommendation ITU-R S.1428 |
| | -170 | 90 | | |
| | -164 | 99.9 | | |
| | -164 | 100 | | |
| | -156 | 0 | 1 000 | |
| | -156 | 90 | | |
| | -150 | 99.9 | | |
| | -150 | 100 | | |
| | -173 | 0 | 40 | 2 m Recommendation ITU-R S.1428 |
| | -173 | 99.4 | | |
| | -166 | 99.9 | | |
| | -164 | 99.92 | | |
| -164 | 100 | | | |
| -159 | 0 | 1 000 | | |
| -159 | 99.4 | | | |
| -152 | 99.9 | | | |
| -150 | 99.92 | | | |
| -150 | 100 | | | |
| -180 | 0 | 40 | 5 m Recommendation ITU-R S.1428 | |
| -180 | 99.8 | | | |
| -172 | 99.8 | | | |
| -164 | 99.992 | | | |
| -164 | 100 | | | |
| -166 | 0 | 1 000 | | |
| -166 | 99.8 | | | |
| -158 | 99.8 | | | |
| -150 | 99.992 | | | |
| -150 | 100 | | | |

¹ For certain GSO FSS receive earth stations, see also Nos. **9.7A** and **9.7B**.

² For each reference antenna diameter, the limit consists of the complete curve on a plot which is linear in decibels for the epfd_↓ levels and logarithmic for the time percentages, with straight lines joining the data points.

³ A non-GSO system shall meet the limits of this Table in both the 40 kHz and the 1 MHz reference bandwidths.

⁴ For this Table, reference patterns in Recommendation ITU-R S.1428 shall be used only for the calculation of interference from non-GSO FSS systems into GSO FSS systems.

TABLE 1C^{1, 2, 3}Limits on aggregate epfd_↓ radiated by non-GSO FSS systems in certain frequency bands

| Frequency band (GHz) | epfd _↓ (dB(W/m ²)) | Percentage of time during which epfd _↓ may not be exceeded | Reference bandwidth (kHz) | Reference antenna diameter, and reference radiation pattern ⁴ |
|----------------------|---|---|---|--|
| 19.7-20.2 | -182 | 0 | 40 | 70 cm Recommendation ITU-R S.1428 |
| | -172 | 90 | | |
| | -154 | 99.94 | | |
| | -154 | 100 | | |
| | -168 | 0 | 1 000 | |
| | -158 | 90 | | |
| | -140 | 99.94 | | |
| | -140 | 100 | | |
| | -185 | 0 | 40 | 90 cm Recommendation ITU-R S.1428 |
| | -176 | 91 | | |
| | -165 | 99.8 | | |
| | -160 | 99.8 | | |
| -154 | 99.99 | | | |
| -154 | 100 | | | |
| -171 | 0 | 1 000 | | |
| -162 | 91 | | | |
| -151 | 99.8 | | | |
| -146 | 99.8 | | | |
| -140 | 99.99 | | | |
| -140 | 100 | | | |
| -191 | 0 | 40 | 2.5 m Recommendation ITU-R S.1428 | |
| -162 | 99.933 | | | |
| -154 | 99.998 | | | |
| -154 | 100 | | | |
| -177 | 0 | 1 000 | | |
| -148 | 99.933 | | | |
| -140 | 99.998 | | | |
| -140 | 100 | | | |
| -195 | 0 | 40 | 5 m Recommendation ITU-R S.1428 | |
| -184 | 90 | | | |
| -175 | 99.6 | | | |
| -161 | 99.984 | | | |
| -154 | 99.9992 | | | |
| -154 | 100 | | | |
| -181 | 0 | 1 000 | | |
| -170 | 90 | | | |
| -161 | 99.6 | | | |
| -147 | 99.984 | | | |
| -140 | 99.9992 | | | |
| -140 | 100 | | | |

¹ For certain GSO FSS receive earth stations, see also Nos. 9.7A and 9.7B.

² For each reference antenna diameter, the limit consists of the complete curve on a plot which is linear in decibels for the epfd_↓ levels and logarithmic for the time percentages, with straight lines joining the data points.

³ A non-GSO system shall meet the limits of this Table in both the 40 kHz and the 1 MHz reference bandwidths.

⁴ For this Table, reference patterns in Recommendation ITU-R S.1428 shall be used only for the calculation of interference from non-GSO FSS systems into GSO FSS systems.

TABLE 1D^{1,2}

Limits on aggregate epfd_{\downarrow} radiated by non-GSO FSS systems in certain frequency bands into 30 cm, 45 cm, 60 cm, 90 cm, 120 cm, 180 cm, 240 cm and 300 cm BSS antennas

| Frequency band (GHz) | epfd_{\downarrow} (dB(W/m ²)) | Percentage of time during which epfd_{\downarrow} may not be exceeded | Reference bandwidth (kHz) | Reference antenna diameter, and reference radiation pattern ³ |
|--|--|--|---|--|
| 11.7-12.5 in Region 1 11.7-12.2 and 12.5-12.75 in Region 3 12.2-12.7 in Region 2 | -160.4 | 0 | 40 | 30 cm Recommendation ITU-R BO.1443, Annex 1 |
| | -160.1 | 25 | | |
| | -158.6 | 96 | | |
| | -158.6 | 98 | | |
| | -158.33 | 98 | | |
| | -158.33 | 100 | | |
| | -170 | 0 | 40 | 45 cm Recommendation ITU-R BO.1443, Annex 1 |
| | -167 | 66 | | |
| | -164 | 97.75 | | |
| | -160.75 | 99.33 | | |
| | -160 | 99.95 | | |
| | -160 | 100 | | |
| | -171 | 0 | 40 | 60 cm Recommendation ITU-R BO.1443, Annex 1 |
| | -168.75 | 90 | | |
| | -167.75 | 97.8 | | |
| | -162 | 99.6 | | |
| | -161 | 99.8 | | |
| | -160.2 | 99.9 | | |
| | -160 | 99.99 | | |
| | -160 | 100 | | |
| -173.75 | 0 | 40 | 90 cm Recommendation ITU-R BO.1443, Annex 1 | |
| -173 | 33 | | | |
| -171 | 98 | | | |
| -165.5 | 99.1 | | | |
| -163 | 99.5 | | | |
| -161 | 99.8 | | | |
| -160 | 99.97 | | | |
| -160 | 100 | | | |
| -177 | 0 | 40 | 120 cm Recommendation ITU-R BO.1443, Annex 1 | |
| -175.25 | 90 | | | |
| -173.75 | 98.9 | | | |
| -173 | 98.9 | | | |
| -169.5 | 99.5 | | | |
| -167.8 | 99.7 | | | |
| -164 | 99.82 | | | |
| -161.9 | 99.9 | | | |
| -161 | 99.965 | | | |
| -160.4 | 99.993 | | | |
| -160 | 100 | | | |

TABLE 1D^{1, 2} (end)

| Frequency band (GHz) | epfd _↓ (dB(W/m ²)) | Percentage of time during which epfd _↓ may not be exceeded | Reference bandwidth (kHz) | Reference antenna diameter, and reference radiation pattern ³ |
|--|---|---|---------------------------|--|
| 11.7-12.5 in Region 1 11.7-12.2 and 12.5-12.75 in Region 3 12.2-12.7 in Region 2 | -179.5 | 0 | 40 | 180 cm Recommendation ITU-R BO.1443, Annex 1 |
| | -178.66 | 33 | | |
| | -176.25 | 98.5 | | |
| | -163.25 | 99.81 | | |
| | -161.5 | 99.91 | | |
| | -160.35 | 99.975 | | |
| | -160 | 99.995 | | |
| | -160 | 100 | 40 | 240 cm Recommendation ITU-R BO.1443, Annex 1 |
| | -182 | 0 | | |
| | -180.9 | 33 | | |
| | -178 | 99.25 | | |
| | -164.4 | 99.85 | | |
| | -161.9 | 99.94 | | |
| | -160.5 | 99.98 | | |
| | -160 | 99.995 | | |
| | -160 | 100 | 40 | 300 cm Recommendation ITU-R BO.1443, Annex 1 |
| | -186.5 | 0 | | |
| | -184 | 33 | | |
| | -180.5 | 99.5 | | |
| | -173 | 99.7 | | |
| | -167 | 99.83 | | |
| -162 | 99.94 | | | |
| -160 | 99.97 | | | |
| -160 | 100 | | | |

¹ For BSS antenna diameters of 180 cm, 240 cm and 300 cm, in addition to the aggregate limits shown in Table 1D, the following aggregate 100% of the time epfd_↓ limits also apply:

| 100% of the time epfd _↓ (dB(W/(m ² · 40 kHz))) | Latitude (North or South) (degrees) |
|--|-------------------------------------|
| -160 | 0 ≤ Latitude ≤ 57.5 |
| -160 + 3.4(57.5 - Latitude)/4 | 57.5 < Latitude ≤ 63.75 |
| -165.3 | 63.75 < Latitude |

² For each reference antenna diameter, the limit consists of the complete curve on a plot which is linear in decibels for the epfd_↓ levels and logarithmic for the time percentages, with straight lines joining the data points. For BSS antenna of diameter 240 cm, in addition to the above aggregate 100% of the time epfd_↓ limit, a -167 dB(W/(m² · 40 kHz)) aggregate 100% of the time operational epfd_↓ limit also applies to receive antennas located in Region 2, west of 140° W, north of 60° N, pointing toward GSO BSS satellites at 91° W, 101° W, 110° W, 119° W and 148° W with elevation angles greater than 5°. This limit is implemented during a transition period of 15 years.

³ For this Table, reference ep patterns in the Annex 1 to Recommendation ITU-R BO.1443 shall be used only for the calculation of interference from non-GSO FSS systems into GSO BSS systems.